


G-Fix Plain Split-ring pipe clamps are designed with integral fixing nuts and suitable for ceiling suspension or vertical wall mounting of piping.



**Material :** Steel

**Finish :** Electrogalvanised post manufacture.

**Options :** Hot Dip Galvanised Finish (Suffix 'HDG').  
Zinc Flake finish (Suffix 'ZF')

**Compliance :** EG to ASTM B633 SC3,  
BS 1706 FE/ZN 12

UL listed Plain Split Clamps (GFSC-UL)  
are available on application.

**Underwriter's Laboratories (UL)**  
UL Listed for sizes ½" to 3"

**Dual-Thread Nut** – G-Fix Plain Split clamps for pipe with ODs 15 mm onwards have M8 + M10 dual-thread suspension nuts.

**Installation Guidelines :** Make sure to install the G-Fix Plain split clamps using a lock-nut in the threaded suspension rod above the fixing nut. This is to facilitate alignment with respect to pipe. Please do not attempt to align the clamp by turning it forcefully, this might damage the clamps top welded nut.

While installing these split clamps on vertical pipes, it is not recommended to subject the welded suspension nut to the load in shear. Separate anchor should carry the total weight of the riser pipe.

SELECTION TABLE FOR G-FIX PLAIN SPLIT CLAMPS

Model	Fixing Nut Size	Steel Nominal		Clamp Range (mm)	UPVC/PPR/ Other Plastic Pipe OD(mm)	Max Load (kg)
		In	mm			
GFSC 1/2"(22mm)	M8 + M10	1/2"	15	20-25mm	17, 20, 21	125
GFSC 3/4"(27mm)	M8 + M10	3/4"	20	26-30mm	25, 27	125
GFSC 1"(34mm)	M8 + M10	1"	25	32-36mm	32, 33	125
GFSC 1 1/4"(42mm)	M8 + M10	1 1/4"	32	38-43mm	40, 42	125
GFSC 1 1/2"(48mm)	M8 + M10	1 1/2"	40	47-51mm	48, 50	125
GFSC 54mm	M8 + M10			53-58mm		125
GFSC 2"(60mm)	M8 + M10	2"	50	60-64mm	60, 63	125
GFSC 70mm	M8 + M10			68-72mm	70	150
GFSC 2 1/2"(73mm)	M8 + M10	2 1/2"	65	74-80mm	75	150
GFSC 83mm	M8 + M10			81-86mm		150
GFSC 89mm	M8 + M10	3"	80	87-92mm	88	150
GFSC 3 1/2"(102mm)	M8 + M10	3 1/2"	90	99-105mm		150
GFSC 110mm	M8 + M10			107-112mm	110	150
GFSC 4"(114mm)	M8 + M10	4"	100	113-118mm	114	150
GFSC 125mm	M8 + M10			125-130mm	125	200
GFSC 5"(140mm)	M8 + M10	5"	125	138-142mm	140	200
GFSC 160mm	M8 + M10			159-166mm	160	200
GFSC 6"(168mm)	M8 + M10	6"	150	168-172mm	168	200
GFSC 200mm	M8 + M10			200-212mm	200	200
GFSC 8"(219mm)	M8 + M10	8"	200	215-220mm	219	200
GFSC 10"(273mm)	M8 + M10	10"	250	269-274mm	273	300

\*\*\* Product specifications are subject to change without prior notice.